

ジブ 長さ	ジブ 角度	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	78°	80°	
25m	主巻	定格荷重 (t)	40.5	42.5	45.5	49.0	53.5	59.5	67.5	79.0	96.0	123.5	15.0	
		作業半径 (m)	25.7	24.6	23.3	21.9	20.3	18.6	16.8	14.9	12.9	10.9	9.6	8.8
		アウトリーチ (m)	18.2	17.1	15.8	14.4	12.8	11.1	9.3	7.4	5.4	3.4	2.1	1.3
		最大揚程 (m)	10.9	12.8	14.6	16.2	17.8	19.1	20.4	21.4	22.3	23.0	23.4	23.6
	補巻	定格荷重 (t)	22.1	23.2	24.6	26.4	28.8	31.9	36.0	42.8	50.0			
		作業半径 (m)	29.6	28.3	26.9	25.3	23.5	21.6	19.5	17.3	15.1	12.7	11.2	10.2
		アウトリーチ (m)	22.1	20.8	19.4	17.8	16.0	14.1	12.0	9.8	7.6	5.2	3.7	2.7
		最大揚程 (m)	12.2	14.4	16.5	18.5	20.3	21.9	23.4	24.7	25.8	26.7	27.1	27.3
31m	主巻	定格荷重 (t)	32.5	34.5	36.5	39.5	43.5	48.5	55.0	64.5	78.5	101.5	124.0	
		作業半径 (m)	30.9	29.5	27.9	26.1	24.2	22.1	19.8	17.5	15.0	12.4	10.9	9.8
		アウトリーチ (m)	23.4	22.0	20.4	18.6	16.7	14.6	12.3	10.0	7.5	4.9	3.4	2.3
		最大揚程 (m)	13.9	16.3	18.4	20.5	22.4	24.1	25.6	26.9	28.0	28.8	29.3	29.5
	補巻	定格荷重 (t)	16.9	17.8	18.9	20.4	22.2	24.6	27.9	32.5	39.2	50.0		
		作業半径 (m)	34.8	33.2	31.5	29.5	27.4	25.0	22.5	19.9	17.1	14.2	12.5	11.3
		アウトリーチ (m)	27.3	25.7	24.0	22.0	19.9	17.5	15.0	12.4	9.6	6.7	5.0	3.8
		最大揚程 (m)	15.2	17.9	20.4	22.7	24.9	26.9	28.6	30.1	31.4	32.5	33.0	33.3