

定格総荷重表

種類および型式		BM800G 浮きクレーン型 ジブ(補助シーブ装着)										単位:t									
ブーム長さ		12.2m		15.2m		18.3m		21.3m		24.4m		27.4m		30.5m		33.5m		36.6m		ブーム長さ	
作業 半 径 (m)	4.0	4.2m	54.3	4.9m	45.8															4.0	
	5.0		45.1		44.9	5.6m	39.7														5.0
	6.0		37.2		37.0		36.9	6.3m	34.8												6.0
	7.0		31.5		31.3		31.2		31.0	30.9	7.6m	28.1									7.0
	8.0		26.6		26.7		26.6		26.5	26.4		26.3	8.3m	25.0							8.0
	9.0		22.4		23.0		22.8		22.7	22.6		22.5		22.4	22.3	9.7m	19.8				9.0
	10.0		19.1		19.9		19.9		19.8	19.7		19.6		19.5	19.4		19.3				10.0
	12.0	11.8m	13.3		15.3		15.5		15.4	15.3		15.2		15.1	15.0		14.9				12.0
	14.0				11.5		12.1		12.2	12.3		12.2		12.1	12.0		11.9				14.0
	16.0			14.5m	10.2		9.5		10.0	10.3		10.5		10.4	10.3		10.2				16.0
	18.0					17.1m	7.8		8.3	8.6		8.8		8.8	8.7		8.5				18.0
	20.0							19.8m	6.7	7.3		7.4		7.5	7.4		7.3				20.0
	22.0									5.9		6.4		6.5	6.5		6.4				22.0
	24.0										22.4m	5.6		5.2	5.5		5.5				24.0
	26.0												25.0m	4.7		4.5	4.7				26.0
	28.0														27.7m	3.9	3.9				28.0
	30.0																3.3				30.0
32.0															30.3m	3.2				32.0	
34.0																	33.0m			34.0	
最大ブーム角度		77°		77°		77°		77°		77°		77°		77°		77°		77°		最大ブーム角度	
最小ブーム角度		30°		30°		30°		30°		30°		30°		30°		30°		30°		最小ブーム角度	
標準掛数		5		5		4		4		3		3		3		3		2		標準掛数	