

定格総荷重表

種類および型式		BM800G 浮きクレーン型 補助シーブ(ジブに55t主フック装着)										単位:t
ブーム長さ		12.2m	15.2m	18.3m	21.3m	24.4m	27.4m	30.5m	33.5m	36.6m	ブーム長さ	
作業半径(m)	5.0	11.0	5.7m 11.0								5.0	
	6.0	11.0	11.0	6.4m 11.0							6.0	
	7.0	11.0	11.0	11.0	11.0	7.7m 11.0					7.0	
	8.0	11.0	11.0	11.0	11.0	11.0	8.4m 11.0				8.0	
	9.0	11.0	11.0	11.0	11.0	11.0	11.0	9.1m 11.0	9.8m 11.0		9.0	
	10.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	10.5m 11.0	10.0	
	12.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	12.0	
	14.0	12.7m 10.2	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	14.0	
	16.0		15.3m 7.9	9.3	9.8	10.1	10.3	10.2	10.1	10.0	16.0	
	18.0			6.2	8.1	8.4	8.6	8.6	8.5	8.3	18.0	
	20.0				6.3	7.0	7.1	7.2	7.2	7.1	20.0	
	22.0				20.6m 5.8	5.7	5.9	6.0	6.0	6.0	22.0	
	24.0					23.2m 4.7	4.9	5.0	5.0	5.0	24.0	
	26.0						25.9m 4.0	4.1	4.2	4.0	26.0	
	28.0							3.3	3.4	3.4	28.0	
	30.0							28.5m 3.2	2.8	2.8	30.0	
32.0								31.2m 2.4	2.2	32.0		
34.0									33.8m 1.7	34.0		
最大ブーム角度		77°	77°	77°	77°	77°	77°	77°	77°	77°	最大ブーム角度	
最小ブーム角度		30°	30°	30°	30°	30°	30°	30°	30°	30°	最小ブーム角度	
標準掛数		1	1	1	1	1	1	1	1	1	標準掛数	