

ジブ長さ	ジブ角度	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	30.0°	34.6°	39.2°	43.3°	47.1°	50.6°	54.0°	57.2°	60.3°	63.3°	66.3°	69.1°	71.9°	74.6°	77.1°	
22m	主巻	定格荷重 (t)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	88.8	93.0	99.0	105.0	111.5	118.8	127.0	136.2	146.6	158.5	172.3	188.3	207.2	230.0	250.0
		作業半径 (m)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	23.0	22.0	21.0	20.0	19.0	18.0	17.0	16.0	15.0	14.0	13.0	12.0	11.0	10.0	9.0
ジブ長さ	ジブ角度	-	-	-	-	-	-	-	-	-	-	-	30.0°	34.4°	38.0°	41.3°	44.4°	47.3°	50.1°	52.8°	55.3°	57.8°	60.3°	62.6°	64.9°	67.2°	69.4°	71.6°	73.8°	75.9°	77.0°	-
28m	主巻	定格荷重 (t)	-	-	-	-	-	-	-	-	-	-	67.4	70.9	74.4	78.3	82.3	86.7	91.6	97.0	103.0	109.5	116.8	125.0	134.2	144.6	156.5	170.3	186.3	203.0	205.0	-
		作業半径 (m)	-	-	-	-	-	-	-	-	-	-	28.0	27.0	26.0	25.0	24.0	23.0	22.0	21.0	20.0	19.0	18.0	17.0	16.0	15.0	14.0	13.0	12.0	11.0	10.0	-
ジブ長さ	ジブ角度	-	-	-	-	-	30.0°	34.2°	37.2°	40.0°	42.6°	45.1°	47.5°	49.8°	52.0°	54.1°	56.2°	58.2°	60.2°	62.2°	64.1°	65.9°	67.8°	69.6°	71.4°	73.2°	75.0°	76.9°	-	-	-	
34m	主巻	定格荷重 (t)	-	-	-	-	-	51.5	54.6	57.1	59.8	62.8	65.7	68.9	72.4	76.3	80.3	84.7	89.6	95.0	101.0	107.5	114.8	123.0	132.2	142.6	154.5	159.7	165.0	-	-	-
		作業半径 (m)	-	-	-	-	-	33.0	32.0	31.0	30.0	29.0	28.0	27.0	26.0	25.0	24.0	23.0	22.0	21.0	20.0	19.0	18.0	17.0	16.0	15.0	14.0	13.0	12.0	-	-	-
ジブ長さ	ジブ角度	30.0°	34.1°	36.7°	39.1°	41.3°	43.5°	45.6°	47.6°	49.5°	51.4°	53.2°	55.0°	56.8°	58.5°	60.2°	61.8°	63.5°	65.1°	66.6°	68.2°	69.8°	71.3°	72.8°	74.3°	75.8°	77.0°	-	-	-	-	
40m	主巻	定格荷重 (t)	40.0	42.3	44.1	46.0	48.1	50.3	52.6	55.1	57.8	60.8	63.7	66.9	70.4	74.3	78.3	82.7	87.6	93.0	99.0	105.5	112.8	120.0	123.1	126.3	129.5	132.0	-	-	-	-
		作業半径 (m)	38.0	37.0	36.0	35.0	34.0	33.0	32.0	31.0	30.0	29.0	28.0	27.0	26.0	25.0	24.0	23.0	22.0	21.0	20.0	19.0	18.0	17.0	16.0	15.0	14.0	13.0	-	-	-	-